

TECHNICAL DATA SHEET




DMX Drain 2000™ Drainage Membrane

MATERIAL

DMX uses a specially formulated Polypropylene that provides a high environmental stress crack resistance to alkalines and acids found in the soil. In addition, DMX is made from 50% recycled resin. Our special extrusion process utilizes low heat and low shear to prevent heat degradation in the final product. The use of antioxidants and lubricants further ensure a smooth, superior quality membrane that outperforms the competition.

PROPERTIES

The DMX Drain 2000™ drainage board finished product has a 10mm dimple height, providing a drainage capacity of 18 gal/min/ft of width and a compressive strength of 11,000lbs/sq ft. Polyethylene is highly resistant to chemical interaction and has a life expectancy of up to 50 years when properly installed in accordance with the manufacturer's instructions.



TECHNICAL DATA

DRAINAGE CORE	TEST METHOD	IMPERIAL	METRIC
Colour	Black		
Dimensions (W x L)		4 x 50ft, 6 x 50ft	1.22 x 15.25m, 1.83 x 15.25m
Compressive Strength	ASTM D 1621	11000 psf	527 kNm ²
Thickness	ASTM D 1777	1/4 inch	6.35 mm
Material	Woven Polypropylene		
FILTER FABRIC	NON-WOVEN		
Grab Tensile	ASTM D 4632	100 lbs md/cd	.45 k N md/cd
Trapezoidal Tear	ASTM D 4533	50 lbs md/cd	222 N md/cd
Puncture Strength	ASTM D 4833	65 lbs	.29 kN
Permeability	ASTM D 3786	225 psi	1551 kPa
AOS	ASTM D 4751	70 Sieve	210 micron
Permittivity	ASTM D 4491	2.6 Sec -1	2.6 Sec -1
Water Flow Rate	ASTM D 4491	140 gal/min/ft ²	5704 L/min/m ²
Weight Typical	ASTM D 5261	4.0 oz/yd ²	
Material	Polypropylene		
COMPOSITE SYSTEM			
Water Flow Rate (V)	ASTM D 4716	18 Gal/min/ft	223 L/min/m
Roll Size		4ft x 50ft, 6ft x 50ft	1.22m x 15.25m, 1.83m x 15.25m
Roll Weight		28 lbs	12.7 kg