

## TECHNICAL DATA SHEET




### DMX Drain 6000™ Drainage Membrane

#### MATERIAL

DMX uses a specially formulated Polypropylene that provides a high environmental stress crack resistance to alkalines and acids found in the soil. In addition, DMX is made from 50% recycled resin. Our special extrusion process utilizes low heat and low shear to prevent heat degradation in the final product. The use of antioxidants and lubricants further ensure a smooth, superior quality membrane that outperforms the competition.

#### PROPERTIES

The DMX Drain 6000™ drainage board finished product has a 10mm dimple height, providing a drainage capacity of 18 gal/min/ft of width and a compressive strength of 15,000lbs/sq ft. Polyethylene is highly resistant to chemical interaction and has a life expectancy of up to 50 years when properly installed in accordance with the manufacturer's instructions.



#### TECHNICAL DATA

DRAINAGE CORE		TEST METHOD	IMPERIAL	METRIC
Colour	Black			
Dimensions (W x L)			4 x 50ft, 6 x 50ft	1.22 x 15.25m, 1.83 x 15.25m
Compressive Strength	ASTM D 1621		15000 psf	718 kNm <sup>2</sup>
Thickness	ASTM D 1777		7/16 inch	11 mm
Material	Polypropylene			
FILTER FABRIC		NON-WOVEN		
Grab Tensile	ASTM D 4632		100 lbs md/cd	.45 kN md/cd
Trapezoidal Tear	ASTM D 4533		65 lbs md/cd	.30 kN md/cd
Puncture Strength	ASTM D 4833		65 lbs	.30 kN
Permeability	ASTM D 3786		210 psi	1447kPa
AOS	ASTM D 4751		70 Sieve	210 micron
Permittivity	ASTM D 4491		1.8 Sec -1	1.8 Sec -1
Water Flow Rate	ASTM D 4491		140 gal/min/ft <sup>2</sup>	5704 L/min/m <sup>2</sup>
Weight Typical	ASTM D 5261		4.0 oz/yd <sup>2</sup>	135 g/m <sup>2</sup>
Material	Polypropylene			
COMPOSITE SYSTEM				
Water Flow Rate (V)	ASTM D 4716		18 Gal/min/ft	223 L/min/m
Roll Size			4ft x 50ft, 6ft x 50ft	1.22m x 15.25m, 1.83m x 15.25m
Roll Weight			40 lbs, 55 lbs	18 kg, 25 kg